

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number
WO 2004/005091 A1

(51) International Patent Classification⁷: **B60T 1/087**,
F16D 57/04

JÖNSSON, Hans [SE/SE]; Stålhamravägen 52, S-151
47 Södertälje (SE). HERMELIN, Gunnar [SE/SE];
Gotthemsvägen 8, S-151 39 Södertälje (SE).

(21) International Application Number:
PCT/SE2003/000987

(74) Agent: FORSELL, Hans; Scania CV AB, Patents, S-151
87 Södertälje (SE).

(22) International Filing Date: 13 June 2003 (13.06.2003)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0202085-7 3 July 2002 (03.07.2002) SE

(71) Applicant (for all designated States except US): SCANIA
CV AB (publ) [SE/SE]; S-151 87 Södertälje (SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.


(72) Inventors; and

(75) Inventors/Applicants (for US only): FÄRM, Johnny
[SE/SE]; Fruängsgatan 29, S-129 51 Hägersten (SE).

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: HYDRODYNAMIC BRAKE



(57) Abstract: The present invention relates to a hydrodynamic brake which comprises a stator (1), a rotor (2), a toroidal space (7) defined by the stator (1) and the rotor (2), a medium which is intended to be supplied to the toroidal space (7) when the brake is activated, and a multiplicity of components (24-33) for allowing regulation of the flow of said medium to and from the toroidal space (7). The hydrodynamic brake incorporates a structure with a multiplicity of recesses (14-23) which each have an opening in a substantially common plane (A) and are each intended to accommodate one of said components (24-33).

WO 2004/005091 A1



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

Hydrodynamic brake

BACKGROUND TO THE INVENTION, AND STATE OF THE ART

5 The invention relates to a hydrodynamic brake according to the preamble of claim 1.

Hydrodynamic brakes such as retarders incorporate not only a stator and a rotor but also a number of components which are necessary for ensuring proper functioning of the retarder. Such components may comprise valves of various kinds which regulate
10 the oil flow in a number of pipe circuits for the retarder. Another component is a pump (which may be a gear pump) which is required for transferring oil from an oil sump. A further component is an accumulator which caters for rapid filling of the retarder when necessary. Conventional retarders are usually constructed in such a way that the majority of said components are relatively dispersed in the retarder. This
15 renders the fitting and servicing of components of a conventional retarder laborious and relatively complicated.

SUMMARY OF THE INVENTION

20 The object of the present invention is to provide a hydrodynamic brake which is so constructed that the majority of the brake's constituent components are very easily accessible so that fitting and servicing become easy and take relatively little time.

This object is achieved with the hydrodynamic brake of the kind mentioned in the
25 introduction which is characterised by the features indicated in the characterising part of claim 1. The fact that the hydrodynamic brake comprises a structure with a multiplicity of recesses which have openings arranged in a substantially common plane renders these components very easily accessible. Dismantling the hydraulic brake for access to such a plane which incorporates recesses for the various components can be
30 made very simple and involve only a small number of working operations. It becomes easy to remove the components from the recesses and check them and, where

necessary, substitute new ones. The fitting and servicing of the components arranged in such recesses can thus be done quickly and easily.

According to a preferred embodiment of the present invention, said structure is
5 incorporated in a first element of the hydrodynamic brake, and a second element of the hydrodynamic brake is detachably fittable along a connecting region to the first element so that said elements in a fitted state form a housing which entirely surrounds said components. Access to said plane is then by removing the second element, which can be done in a relatively uncomplicated manner by using suitable fastenings. With
10 advantage, the connecting region has an extent in said plane. Removal of the second element provides immediate access to said spaces which accommodate the various components. A gasket is preferably arranged in the connecting region between said first and second elements of the housing. Such a gasket results in a sealed housing which surrounds said components and prevents the enclosed medium from leaking out.

15 According to another preferred embodiment of the present invention, at least one of said components is a valve means. A hydrodynamic brake incorporates a number of valves of various kinds which are necessary for the functioning of the hydrodynamic brake. With advantage, substantially all such valves are arranged in spaces which have
20 an opening in said plane. Such valves may comprise a regulating valve, a safety valve and check valves with various functions. One of said components may be a gear pump. A gear pump is of simple design and can with advantage be arranged in such a space. Another of said components may be an accumulator. In this case the recess may be of an appropriate shape for storing the medium at high pressure.

25 According to another preferred embodiment of the present invention, the hydrodynamic brake incorporates a storage space for the medium. As the first element and the second element form a completely sealed enclosure of said components, it is advantageous that a storage space for the medium be incorporated in said housing.
30 The medium is preferably an oil and the storage space may therefore be described as an oil sump. With advantage, the first element incorporates the stator and the rotor, and the second element is of cover-like design. In this case the cover-like second

element may be easily detachable from the first element so as to provide access to said recesses. The first element and the second element may be mouldings made of a suitable material. The first element may have moulded recesses with a shape entirely adapted to the specific components to be accommodated in the recesses. The first
5 element preferably incorporates at least one duct to allow transfer of the medium. The first element may incorporate a structure which comprises, adjacent to the recesses, a multiplicity of readymade ducts for transfer of the medium. There is thus substantially no need to arrange any separate ducts for allowing transport of the medium in the first element.

BRIEF DESCRIPTION OF THE DRAWING

A preferred embodiment of the invention is described below by way of example with reference to the attached drawing, in which:

Fig. 1 depicts a section through a retarder according to the present invention,

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT OF THE INVENTION

Fig. 1 depicts a hydrodynamic brake in the form of a retarder of a powered vehicle. The retarder comprises a stator 1 and a rotor 2. The stator 1 has an annular shell 3 with a multiplicity of blades 4 arranged at uniform spacing along the annular shell 3. The rotor 2 is of corresponding design with an annular shell 5 which incorporates a
25 multiplicity of blades 6 likewise arranged at uniform spacing along the annular shell 5. The respective shells 3, 5 of the stator 1 and rotor 2 are coaxially arranged with respect to one another so that they together form a toroidal space 7. The rotor 2 incorporates a shaft portion 8 which is firmly connected to a rotatable shaft 9. The rotatable shaft 9 is itself connected to an appropriate driveshaft of the vehicle's driveline. The rotor 2 will
30 thus rotate together with the vehicle's driveline

The retarder depicted in Fig. 1 incorporates a housing which comprises a first element 10 and a second element 11. The first element 10 incorporates a body in which inter alia the stator 1 and the rotor 2 are arranged. The second element 11 is of cover-like design and can be fitted detachably along a connecting region 12 to the first element 10 so that in a fitted state they form a closed housing. In the connecting region 12, a gasket 13 is arranged so that the housing forms a sealed enclosure. The first element 10 incorporates a multiplicity of recesses 14-23 which each have an opening in a substantially common plane A represented by the broken line A-A in Fig. 1. The connecting region 12 of the first element 10 and second element 11 also has an extent in said plane A.

The recesses 14-23 are each designed to accommodate a component which forms part of the retarder. The shape and size of the recesses 14-23 are adapted to the respective specific components which they accommodate. A first such recess 14 accommodates a first check valve 24. A second recess 15 accommodates an outlet check valve 25. A third recess 16 accommodates a gear pump 26. A fourth recess 17 accommodates a second check valve 27. A fifth recess 18 accommodates a dump (rapid emptying) valve 28. A sixth recess 19 accommodates a regulating valve 29. A seventh recess 20 accommodates an inlet check valve 30. An eighth recess 21 accommodates a filling valve 31. A ninth recess 22 accommodates an intake valve 32 for filling an accumulator 33. A tenth recess 23 accommodates said accumulator 33. The first element 10 and the second element 11 thus form a sealed housing which incorporates an oil sump 34 for storage of oil.

The retarder incorporates a first pipe circuit 35 with a first portion 35a which leads the oil from an outlet from the toroidal space 7 to the outlet check valve 25. A second portion 35b of the first pipe circuit leads the oil from the outlet check valve 25 to a heat exchanger 36 to cool the oil. A third portion 35c of the first pipe circuit leads the cooled oil to the inlet check valve 30 or alternatively to the regulating valve 29, depending on whether the retarder is or is not activated. A fourth portion 35d of the first pipe circuit leads the oil to an inlet to the toroidal space 7. The retarder incorporates a second pipe circuit 37 with a first portion 37a via which the oil is drawn

from the oil sump 34 to the gear pump 26. A second portion 37b of the second pipe circuit 37 leads the oil to the first check valve 24 and the second check valve 27.

When the retarder is not activated, the oil is led via the first check valve 24 and a third portion 37c of the second pipe circuit to the second portion 35b of the first pipe circuit.

5 If the retarder is activated, the oil is led instead via the second check valve 27 and a fourth portion 37d of the second pipe circuit to an inlet to the toroidal space 7. The retarder also incorporates a third pipe circuit 38 which connects the accumulator 33 to a fourth portion 35d of the first pipe circuit. The third circuit 38 incorporates the filling valve 31 and the accumulator's intake valve 32. The first element 10 of the
10 housing incorporates, adjacent to the recesses 14-23, occupied ducts which form part of the aforesaid pipe circuits 35, 37, 38.

A first control valve 39 is intended to control, by means of a control pressure, the operation of the safety valve 18 so that the toroidal space 7 can be quickly emptied of
15 oil when necessary. A proportional valve 40 is intended to control, by means of a control pressure, the operation of the regulating valve 19 in order to activate the retarder and regulate the retarder's braking action. A second control valve 41 is intended to control, by means of a control pressure, the operation of the accumulator 33 so as to fill the toroidal space quickly with oil in order to effect a rapid braking
20 action of the retarder. All of these three control valves 39, 40, 41 and the heat exchanger 36 are situated outside the housing.

When the vehicle's driver does not require the vehicle to be subjected to any braking action, the proportional valve 40 supplies no control pressure to the regulating valve
25 29, which opens fully so that any oil in the third portion 37c of the first pipe circuit drains away, via a passage 42, to the oil sump 34. This means that no oil runs past the inlet check valve 30, which requires relatively high oil pressure for it to open and lead oil to the toroidal space 7. As in this situation no oil is led to the toroidal space 7, substantially no braking action is effected other than a minor undesired braking action
30 due to a so-called no-load loss caused by the rotor circulating the air present in the toroidal space 7.

The driveshaft 9 also drives the gear pump 26 which continuously pumps oil from the oil sump 34 during operation of the vehicle. From the gear pump 26, the oil is led at a positive pressure to the second portion 37b of the second pipe circuit. The first check valve 24 here has a spring with preloading such that it opens at a positive pressure of about 0.5 bar. The second check valve 27 has a spring with preloading such that it opens at a positive pressure of about 2 bar. When the regulating valve 29 is open, there is substantially no positive pressure in the first pipe circuit 35. This means that in the second portion 35b of the first pipe circuit there is no positive pressure which would otherwise increase the opening pressure for the first check valve 24. As the first check valve 24 opens at a lower pressure than the second check valve 27, the oil transferred from the oil sump 34 by the gear pump 26 is only led via the first check valve 24 and the third portion 37c of the second pipe circuit to the second portion 35b of the first pipe circuit, which is thus situated after the toroidal space 7 in the direction of flow of the oil. Thereafter the oil is led back to the oil sump 34 via the heat exchanger 36, the third portion 35c of the first pipe circuit, and the regulating valve 29.

When the vehicle's driver requires the vehicle to be subjected to a braking action, the proportional valve 40 supplies the regulating valve 29 with a control pressure which is greater than the preloading of the inlet check valve 30. The second control valve 41 activates the accumulator 33 so that the latter, via the third pipe circuit 38 and the filling valve 31, leads oil at high pressure to the fourth portion 35d of the first pipe circuit and to the toroidal space 7. The accumulator 33 initiates oil supply by means of a positive pressure to bring about rapid filling of the toroidal space 7 and thereby effect a corresponding rapid braking action of the retarder. After the circulation of the oil in the toroidal space 7, the oil is led out at high pressure via an outlet from the stator 1 to the first portion 35a of the first pipe circuit. The outlet check valve 25 is opened by the high oil pressure and the oil is led to the second portion 35b of the first pipe circuit. At this stage the oil is at a positive pressure of at least 5 bar. The oil in the second portion 35b of the first pipe circuit is also led into the third portion 37c of the second pipe circuit and exerts there a pressure action urging the first check valve 24 towards a closed position. The opening pressure required for the first check valve 24 will thus be higher than the corresponding opening pressure for the second check valve 27 which

had a preloading of about 2 bar. This means that all of the oil transferred by the gear pump 26 from the oil sump 34 will be led via the second check valve 27 and the fourth portion 37d of the second pump circuit to an inlet to the toroidal space 7.

5 The inlet to the toroidal space 7 is with advantage arranged centrally in the toroidal space 7.1. In the central part of the toroidal space a relatively low pressure prevails in substantially all operating states. Using a separate pipe portion 37d to supply the oil from the oil sump 34 at atmospheric pressure to the toroidal space 7 means that this oil need not be pumped up to the high pressure which prevails in the fourth portion 35d of
10 the first pipe circuit. A less expensive gear pump 26 with a smaller pump capacity can therefore be used. The fourth portion 37d of the second pipe circuit may also be of relatively simple design since it need only be dimensioned to carry oil at a relatively small positive pressure.

15 The oil is led from the second portion 35b of the first pipe circuit to the heat exchanger 36, in which it is cooled. The braking action of the retarder is regulated by the control pressure from the proportional valve 40. The position of the regulating valve 29 is adjusted by means of the control pressure from the proportional valve 40 so that a certain proportion of the cooled oil after the heat exchanger 36 is led back to the oil
20 sump 34, while the remainder is led past the inlet check valve 30 to the toroidal space 7. The result is regulation of the amount of oil circulating in the toroidal space 7 so as to effect a desired braking action.

The fact that the retarder incorporates a structure with a multiplicity of recesses 14-23
25 which have openings arranged in a substantially common plane A renders these components 24-33 very easily accessible. Removing the cover-like second element 11 from the first element 10 provides immediate access to the various components 24-33 arranged in the recesses 14-23, without further dismantling work, since the openings of all the recesses 14-23 are situated in a substantially common plane A. This means that
30 the components 24-33 can easily be taken out and serviced or replaced as necessary. In a fitted state, the gasket 13 in the connecting region 12 between the first element 10 and the second element 11 prevents oil in the sump 34 from leaking out. The elements

10, 11 may be made of a suitable material by, for example, a moulding process. The recesses 14-23 may be of specific shape and size appropriate to the respective components 24-33 to be accommodated in the space 14-23.

- 5 The invention is in no way limited to the embodiment described but may be varied freely within the scopes of the claims.

Claims

1. A hydrodynamic brake comprising a stator (1) which has an annular shell (3) with a
5 multiplicity of blades (4), a rotor (2) which has a corresponding annular shell (5) with
a number of blades (6), which annular shells (3, 5) of the rotor (2) and stator (1) are so
arranged that they form a toroidal space (7), a medium which is intended to be
supplied to the toroidal space (7) for a braking action to be effected, and a number of
components (24-33) for allowing regulation of the flow of said medium, characterised
10 in that the hydrodynamic brake incorporates a structure with at least three recesses (14-
23) which each have an opening in a substantially common plane (A) and which are
each intended to accommodate one of said components (24-33).
2. A hydrodynamic brake according to claim 1, characterised in that said recesses are
15 incorporated in a first element (10) of the hydrodynamic brake and that a second
element (11) of the hydrodynamic brake is detachably fittable along a connecting
region (12) to the first element (10) so that said elements (10, 11) in a fitted state form
a housing which surrounds said components.
- 20 3. A hydrodynamic brake according to claim 2, characterised in that the connecting
region (12) has an extent in said plane (A).
4. A hydrodynamic brake according to claim 2 or 3, characterised in that a gasket (13)
is arranged in the connecting region (12) between said first element (10) and said
25 second element (11).
5. A hydrodynamic brake according to any one of the foregoing claims, characterised
in that one of said components is a valve means (24-25, 27-32).
- 30 6. A hydrodynamic brake according to any one of the foregoing claims, characterised
in that one of said components is a gear pump (26).

7. A hydrodynamic brake according to any one of the foregoing claims, characterised in that one of said components is an accumulator (33).

5 8. A hydrodynamic brake according to any one of the foregoing claims, characterised in that the hydrodynamic brake incorporates a storage space (34) for the medium.

9. A hydrodynamic brake according to claim 2, characterised in that the first element (10) incorporates the stator (1) and the rotor (2) and that the second element (11) is of cover-like design.

10

10. A hydrodynamic brake according to any one of the foregoing claims, characterised in that the first element (10) incorporates in its structure at least one duct to allow transfer of the medium.




Fig 1

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/00987

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B60T 1/087, F16D 57/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B60T, F16D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0812746 A2 (VOITH TURBO GMBH & CO. KG), 17 December 1997 (17.12.97), figures 1,2, abstract --	1-10
A	US 6234285 B1 (J. FRIEDRICH ET AL), 22 May 2001 (22.05.01), figures 1,2, abstract --	1-10
A	EP 0970860 A2 (VOITH TURBO GMBH & CO. KG), 12 January 2000 (12.01.00), figure 1, abstract -- -----	1-10

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

23 Sept 2003

Date of mailing of the international search report

25 -09- 2003

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Alexandra Jarlmark / MRo
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

26/07/03

International application No.

PCT/SE 03/00987

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP	0812746	A2	17/12/97	DE	19623679 C	27/11/97
				JP	10061693 A	06/03/98

US	6234285	B1	22/05/01	DE	19623680 A,C	20/02/97
				DE	59704171 D	00/00/00
				EP	0812745 A,B	17/12/97
				SE	0812745 T3	
				JP	10061692 A	06/03/98

EP	0970860	A2	12/01/00	SE	0970860 T3	
				DE	19918701 A	20/01/00
				DE	29811787 U	08/10/98
				DE	59903077 D	00/00/00
				JP	2000041374 A	08/02/00
